AURORA POWER

YF-LFP-35kWh

Product Specifications



Battery Type	LiFePO4
Nominal Energy	35kWh
Nominal Capacity	684Ah
Nominal Voltage	51.2V
Operating Voltage	44.8-56 V
Recommend Charge/Discharge Current	280A/280A
Max. continuous charge/discharge Current	300A
Peak Charge/Discharge Current(@10s)	310A
Parallel	≤16 PCS
Depth Of Discharge(DOD)	≥90%
Display Type	LCD
Protection Level	IP21
Working Temperature Range(Charging)	0 ~ +55°C
Working Temperature Range(Discharging)	-10°C ~ +55°C
Storage Temperature Range(One month)	-10°C ~ +45°C
Storage Temperature Range(Six months)	-10°C ~ +35°C
Altitude	≤2000m
Communication	CAN/RS485
Cycle Life	≥8000 Cycles
Installation	Floor-Mounting
Protection	Built-in smart BMS
Product Dimension	600*440*882mm
Warranty Statement	*BMS warranty: 5 years *Battery cell warranty: 10 years *Test conditions: 0.5C charge/discharge, @25°C, 80% DOD, @25°C, 80% DOD;product specifications are subject to change without prior notice.

YF-LFP-35kWh

Product Specifications



Cycle-life test conditions: 0.5C charge/discharge, 25°C, 80% DOD. Refer to the applicable warranty terms for coverage.