aurora
OPTOELECTRONIC




All In One Solar Street Light

Features

- Smart Street Light Controller
- High Light Efficiency LED Lamp Beads
- Class A Mono PV Modules
- LiFePO4 Battery
- Aviation Aluminum Material
- Adjustable Installation Angle

Product Dimension



Installation Method



Vertical
Single-arm





Vertical
Double-arm

Product Parameter

MODEL	YF-OPTIMUS-100W-D
PV Module	100W Mono
LED Efficiency	230lm/W
LED Chip	SMD 5050 LED
LED Chip Brand	Bridge Lux
Viewing Angle	75°*140°
Color Temperature	3000~6500K, typical value(5500K~6000K)
Battery Type	LiFePO4 battery
Battery Capacity	320WH
Charge Controller	MPPT
Working Mode	Time Dimming
Protection Grade	IP65
Certificate	CE, RoHS
Working Temperature	-20°C~+60°C
Product Dimension(mm)	1270*446*52
Package Dimension(mm)	1319*220*520
Installation Height	5-8m Light Pole
Warranty	5years

Light Curve





Case





aurora
OPTOELECTRONIC

Shenzhen Yufai Aurora Opto. Co., Ltd

www.yufai-aurora.com

www.aurorabattery.com

allanwfng@yufai-aurora.com

13602219599

Dunfa Industrial Zone, Xixiang, Bao'an, Shenzhen

Xiangrong Industrial Park, Dalingshan, Dongguan

www.yufai-aurora.com

www.aurorabattery.com